

Udendørs bussirene

Kode: JA-115A

Sirenen JA-115A er en del af JABLOTRON 100+-systemet. Den bruges til at angive alarmer udendørs og til supplerende akustisk indikation.



Produktbeskrivelse:

Den har en energisparefunktion for det tilfælde, at strømforsyningen svigter, samt et integreret vaterpas, der sikrer en præcis opsatning. Sirenen optager én plads i systemet.

Sirenen kan fås med valgfrit lag i rustfrit stal eller i hvid/gra plastik. Lagene tilbydes med rød eller blå fl. Sirenen er adressérbar og optager én plads i alarmsystemet.

Teknisk information:

Spanding	via centralens BUS 12 V (9 -15 V)
Forbrug ved strømsvigt	5 mA
Forbrug ved opladning af internt batteri	50 mA
Back-up batteri	NiCd pack 4,8 V/1800 mAh
Batteri levetid	ca. 3 år
Sirene	piezo electric, 100 dB/m
Størrelse	300 × 200 × 70 mm
Sikringsklasse	klasse 2 i henhold til EN 50131-1, EN 50131-4
Miljø i henhold til EN 50131-1	IV., indendørs
Drifttemperatur	-25 °C til 60 °C
Tæthed	IP44

JA-165A Tradlos bussirene

The JA-165A siren is a component of the JABLOTRON 100+ system. It is used to indicate alarms outdoors and for supplementary acoustic indication. The siren is powered by a lithium battery, completely without the need of any external power supply.

Power supply	Lithium battery 3.6 V / 13 Ah Type BAT-100A (up to 2 pieces can be fitted)
--------------	---

Typical battery life	approx. 5 years (with default settings)
Operating frequency	868.1 MHz, JABLOTRON protocol
Communication range	approx. 300 m (in the open space)
Antenna	internal (an AN-868 external antenna can be connected)
Piezoelectric siren	100 dB/m (value with a new battery)
Dimensions	200 x 300 x 70 mm (with enclosure)
Classification according to	EN 50131-1, EN 50131-4, class 2
Environment according to	EN 50131-1, IV. General, outdoor
Operating temperature range	-20 °C to +60 °C
Ingress protection class	IP44
in conformity with	ETSI EN 300220, EN 50130-4, EN 55022, EN 60950-1
Operation conditions	ERC REC 70-03