DE 06-12 Power adaptor 12V / 0.5A

Power adaptor with a 1.1 m flexible cable terminated by a plug is intended for powering Jablotron devices like wireless keyboards, GSM communicators or UC receivers etc. The compact dimensions of the case allow installation into a standard electro-installation junction box for hidden installation beneath Jablotron wall-box-mounted products such as the above-mentioned items. The screw holes for M3 screws are also useful for installation in typical junction boxes where fixing is required.



Installation shall always be provided by a qualified electrician.

Technical specifications

Supply voltage	100 ~ 240 V AC, class protection II
Output voltage	12V DC (±2 %)
Output current	500 mA
Peak output current T<5 min	1000 mA
Output power	12 W max.
Short-circuit protection and overload protection	yes
Enclosure protection	IP64
Dimensions	50 x 48 x 25 mm
Input cable	length 110 mm (230 V), diameter 1.3 mm (AWG 16)
Operational conditions according to	EN 50131-1 II. Environmental class
Working temperature range	-10 °C to +40 °C
Complies with	EN 50130-4, EN 55022, EN 60950-1

JABLOTRON ALARMS a.s. hereby declares that the DE06-12 is in a compliance with the relevant Union harmonisation legislation: Directives No: 2014/35/EU, 2014/30/EU, 2011/65/EU. The original of the conformity assessment can be found at www.jablotron.com - Section Downloads.

Note: Disposing of this product correctly will help save valuable resources and prevent any potential negative effects on human health and the environment, which could otherwise arise from inappropriate waste handling. Please return the product to the dealer or contact your local authority for further details of your nearest designated collection point.