CZ CT- 01 roletový detektor

Roletový detektor slouží pro detekci (nežádoucí) manipulace s předokenní roletou, žaluzií a podobně. Jedná se o rohatkový mechanismus, který při pohybu lanka, spojeného s roletou vytváří na svorkách detektoru střídavě rozpojený a spojený kontakt.

Detektor CT-01 je určen pro připojení k bezdrátovému detektoru OASiS JA-81M. Tento bezdrátový detektor má upravený vstup, který filtruje náhodné malé pohyby lanka detektoru CT-01 například při poryvech větru, které mohou pohnout roletou (hlásí poplach, když jsou více než 3 impulsy během 5 sec).

Technické parametry

Výstupní kontakt detektoru	100 mA/60 V
Rozsah pohybu lanka	5 ... 260 cm
Rozměry	94 x 102 x 17 mm
Prostředí dle ČSN EN 50131-1	III. venkovní chráněné
Rozsah pracovních teplot	-25 °C až +50 °C
Maximální délka vodičů k JA-81M	3 m

Detektor je navržen a vyroben ve shodě s na něj se vztahujícími ustanoveními: Nařízení vlády č. 426/2000Sb., je-li použit dle jeho určení. Originál prohlášení o shodě je na www.jablotron.cz v sekci poradenství

Poznámka: *Výrobek, ačkoliv neobsahuje žádné škodlivé materiály, nevyhazujte do odpadků, ale předejte na sběrné místo elektronického odpadu. Podrobnější informace na www.jablotron.cz.*

EN CT- 01 shutter-movement detector

The CT-01 is wired detector for detecting the unauthorised movement of external window shutters on houses or buildings. The string movement turns a ratchet wheel and triggeres a contact inside which makes a series of open – closed pulses at the terminals

The CT-01 wired outputs can be connected to the wired input of an OASiS JA-81M door detector to connect the CT-01 signals to the OASiS alarm system. False alarms caused by the wind moving the shutters are avoided by the door detector only raising the alarm when at least 3 pulses are received from the CT-01 within 5 seconds.

Technical parameters

Output contact of detector	100 mA/60 V
Range of movement	5 to 260 cm
Dimensions	94 x 102 x 17 mm
Environment according to EN 50131-1	III. outside protected
Operating temperature range	-25 °C to +50 °C
Maximum wire length to JA-81M door detector	3 metres

JABLOTRON ALARMS a.s. hereby declares that the CT-01 is in compliance with the essential requirements and other relevant provisions of Directive 1999/5/EC The original of the conformity assessment can be found at www.jablotron.com, Technical Support section

***Note**: Disposing of this product correctly will help save valuable resources and prevent any potential negative effects on human health and the environment, which could otherwise arise from inappropriate waste handling. Please return the product to the dealer or contact your local authority for further details of your nearest designated collection point.*

