The JA-111A RB Bus external siren

Technical specifications

Power	from control panel bus 12 V (9–15 V)
Current consumption in standby mode	5 mA
Current consumption for cable choice	50 mA
Backup battery	NiCd pack 4.8 V/1800 mAh
	lifetime approx. 3 years
	Please note: battery is not included
- minimum loaded voltage	4.0 V
- maximum voltage	6.0 V
Piezoelectric	siren 110 dB/m (with fully charged battery)
Dimensions (with cover)	200 x 300 x 70 mm
Weight (w/o battery)	410 g
Type of warning device	type Z
Classification	Security grade 2
according to	EN 50131-1, EN 50131-4
Environment class	IV, general outdoor, -25 °C to +60 °C
Average operational humidity	75% RH, w/o condensation
Also complies with	EN 50130-4, EN 55032,
	EN IEC 62368-1, EN IEC 63000
Recommended screw	2 x ø 4.5 x 50 mm (countersunk head)
Compatible cover	JA-1x1A-C-xx-x

JABLOTRON ALARMS a.s. hereby declares that the JA-111A RB is in compliance with the relevant European Union harmonisation legislation: Directives No: 2014/35/EU, 2014/30/EU, 2011/65/EU, when used as intended. The original of the conformity assessment can be found at www.jablotron.com – the Downloads section

Note: Disposing of this product correctly will help save valuable resources and prevent any potential negative effects on human health and the environment, which could otherwise arise from inappropriate waste handling. Please return the product to the dealer or contact your local authority for further details of your nearest designated collection point.

The complete version of the manual can be found at:
https://bit.ly/JABLOTRON_JA-111A_RB

JABLOTRON ALARMS a.s.
Pod Skalkou 4567/33 | 46601 Jablonec n. N.
Czech Republic | www.JABLOTRON.com