

Wireless fire and temperature detector

Code: JA-150ST

The JA-150ST optical wireless smoke and temperature detector detects fire inside residential or commercial premises. It allows these settings: smoke and heat, smoke or heat, smoke only, heat only.



Product description:

It has an **alarm memory function** where the LED still lights after the alarm state is over.

It is **battery powered** by alkaline batteries.

It is addressable and occupies one position in the alarm.

Technical information:

Power	3x LR6 (AA) type alkaline batteries, 1.5 V Warning: batteries are not included
Typical battery lifetime	approx. 3 years
Communication band	868.1 MHz, Jablotron protocol
Effective Radiated Power (ERP)	10 mW
Communication range	approx. 300 m (unrestricted area)
Dimensions	diameter 126 mm, height 50 mm
Weight	150 g
Smoke detection	optical light scattering
Smoke detector sensitivity	m = 0.11 - 0.13 dB/m pursuant to EN 54-7
Heat detection	class A2 according to EN 54-5
Alarm temperature	+60 °C to +70 °C
Operating temperature range	-10 °C to +80 °C
Complies with	EN 54-5, EN 54-7, EN 54-25
Also complies with	ETSI EN 300220, EN 50130-4, EN 55022, EN 60950-1
Can be operated according to	ERC REC 70-03
Recommended screw	2x o 3.5 x 40 mm (countersunk head)