

# Wireless magnetic detector with 2 universal inputs

Code: JA-150M

It is a magnetic detector with two configurable independent inputs. The detector is also designed to detect the handling of roller blinds, if it is equipped with a CT-01 roller detector.



## Product description:

Small movements are filtered out so that wind blasts do not cause false alarms. It occupies two separate enrollment addresses in the control panel. The product can be installed by a certified technician with a valid certificate issued by an authorized distributor.

## Technical information:

<b>Power</b>	1x alkaline battery type LR6 (AA) 1.5 V Please note: Battery is not included
<b>Typical battery lifetime</b>	about 2 years
<b>Communication band</b>	868.1 MHz, JABLOTRON protocol
<b>RF range</b>	approx. 300 m (open area)
<b>The maximum length of cable for external detectors</b>	3 m
<b>Maximum radio-frequency power</b>	10 mW
<b>Dimensions</b>	109 x 24 x 22 mm
<b>Classification</b>	Grade 2
<b>According to</b>	EN 50131-1, EN 50131-3, EN 50131-2-6, EN 50131-5-3
<b>Operational environment</b>	EN 50131-1 II. Indoor general
<b>Operational temperature range</b>	-10 °C to +40 °C
<b>Also complies with</b>	ETSI EN 300220, EN 50130-4, EN 55022, EN 50950-1
<b>Can be operated according to</b>	ERC REC 70-03