

# Bus external siren - base with electronics

Code: JA-111A-BASE-RB

It is used for system alarm indication outside a building and as a pre-sensing tamper detector. Replacement for JA-111A – must be ordered with JA-1X1A-C-WH plastic cover.



## Product description:

It can also be used for supplementary acoustic signalling. The siren is equipped with a backup battery which powers the siren during tamper alarm reporting when the connection to the digital bus is severed.

## Technical information:

<b>Power</b>	from control panel BUS 12 V (9...15 V)
<b>Current consumption in standby mode</b>	5 mA
<b>Current consumption for cable choice</b>	50 mA
<b>Backup battery</b>	NiCd pack 4.8 V/1800 mAh lifetime approx. 3 years  Please note: battery is not included
<b>- minimum loaded voltage</b>	4.0 V
<b>- maximum voltage</b>	6.0 V
<b>reusable battery strap</b>	
<b>Piezoelectric siren</b>	110 dB/m (with fully charged battery)
<b>Dimensions (with cover)</b>	200 x 300 x 70 mm
<b>Classification</b>	Security grade 2
<b>according to</b>	EN 50131-1, EN 50131-4
<b>Environment class IV.</b>	general outdoor -25 °C to +60 °C
<b>Security grade</b>	IP44
<b>Also complies with</b>	EN 50130-4, EN 55022, EN 60950-1, EN 50581