

# Bus keypad

Code: JA-110E

It comprises an LCD display, control keys and an RFID reader. It is available in a bus-mounted as well as wireless version. It comprises 4 functional keys for the control of sections, PG outputs and other functions.



## Product description:

The functional keys serve as status indicators at the same time.

- It communicates via a bus and is supplied by it.
- It contains a wired input for the connection of a magnetic detector.
- The keypad is addressable and occupies one position in the security system.
- In a user-friendly menu, it enables comfortable control, management of users and detectors and browsing the event history.

## Technical information:

<b>Power</b>	from control panel digital bus (9...15 V)
<b>Nominal current consumption to calculate back up</b>	30 mA
<b>Current consumption for cable selection</b>	110 mA
<b>Connection type</b>	data BUS – not shared
<b>RFID frequency</b>	125 kHz
<b>Size</b>	120 x 130 x 30 mm
<b>Weight</b>	217 g
<b>Classification</b>	Grade 2 (if selected in the F-Link SW)
<b>according to</b>	EN 50131-1, EN 50131-3, T 031
<b>Operational environment according to</b>	EN 50131-1 II. Indoor general
<b>Operating temperature range</b>	-10 °C to +40 °C
<b>Average operational humidity</b>	75% RH
<b>Certification body</b>	Trezor Test
<b>Complies with</b>	ETSI EN 300330-2, EN 50130-4, EN 55032, EN 60950-1, ETSI EN 301 489
<b>Can be operated according to</b>	ERC REC 70-03