

# Bus combined PIR motion detector with 90° photoverification camera

Code: JA-122PC

This device is a component of the JABLOTRON system. It serves for the detection of human movement in building interiors and visual alarm confirmation. The camera takes colour photos with a resolution of up to 640x480 pixels.



## Product description:

The camera is equipped with a visible flash for taking photos in the dark. The images are saved in the internal memory of the detector and then they are forwarded to the control panel and from the control panel they can be sent to MyJABLOTRON or ARC. The detector can also take a picture by request. The detector takes one position in the system and should be installed by a trained technician with a valid certificate issued by an authorised distributor.

The photo-verification can be used only after registration of the system to MyJABLOTRON or with subsequent ARC service.

## Technical information:

<b>Power</b>	12 V BUS (8... 15 V)
<b>Current consumption:</b>	
- nominal for the backup supply calculation	5 mA
- maximum for cable choice	250 mA (high flash intensity)
<b>Recommended installation height</b>	2,5 m above floor level
<b>PIR detection angle/detection coverage</b>	90°/12 m
<b>Horizontal camera capture angle</b>	90°
<b>Range of the flash</b>	max. 3 meters
<b>Camera resolution</b>	LQ 320x240; HQ 640x480 pixels
<b>Photo size</b>	LQ/HQ 5-20kB/5-64kB
<b>Typical (LQ) photo transmission time to the control panel</b>	up to 20 sec. (10 sec.)
<b>Ideal (HQ) photo transmission time to the control panel</b>	up to 130 sec. (60 sec.)
<b>Typical photo transfer time to server</b>	15 s/GPRS; 2 s/LAN
<b>Dimensions, weight</b>	150 x 65 x 44 mm, 125 g
<b>Classification</b>	Security grade 2/Environmental class II (EN 50131-1)
<b>Operational temperature range</b>	-10 °C to +40 °C

<b>Environment</b>	indoor general
<b>Average operational humidity</b>	75% RH, without condensation
<b>Certification body</b>	Trezor Test s.r.o. (no. 3025)
<b>In compliance with</b>	EN 50131-1, EN 50131-2-2, EN 50130-4, EN 55032, EN IEC 63000.
<b>Recommended screw</b>	2 x o 3.5 x 40 mm (countersunk head)