


# Bus back-up booster unit for JA-100

Code: JA-120Z

Designed for current boosting of the bus, extension of the line length and galvanic isolation of the bus. Output current max. 2A. 2 independent bus output terminal boards - each providing 500 m of bus length.



## Product description:

The product is offered as an electronic module with the JA-83PWR power supply unit. We recommend installation in a PLV-CP-L plastic housing. The product is a component of the JABLOTRON 100+ system, is addressable and occupies one position in the system.

- Output current max. 2A
- 2 independent bus output terminal boards - each providing 500 m of bus length
- The galvanic isolation of the output terminals deals with different ground potentials and safety isolation of the bus
- Back-up battery up to 18 Ah

## Technical information:

<b>Mains power (the JA-83PWR power supply)</b>	90 – 250 V AC
<b>Input power</b>	50 VA
<b>Fuse</b>	T1.6 A/250 V, 5 x 20 mm
<b>Input part</b>	
<b>Powered from the control panel BUS</b>	12 V DC (9 ... 15 V)
<b>Current consumption</b>	
- in standby mode	10 mA
- for cable choice	10 mA
<b>Output part</b>	
<b>Output voltage</b>	typically 13.7 V DC
<b>Maximum ripple</b>	0.1 Vpp
<b>Maximum load current</b>	2 A
<b>Galvanically separated</b>	(testing voltage 4 kV)
<b>General</b>	
<b>Back-up battery 12 V</b>	7 – 18 Ah

<b>Back-up battery type</b>	lead, gel
<b>Low battery level</b>	? 10.9 V
<b>Protection againsts deep discharging</b>	? 9.7 V
<b>Maximum time for charging back-up battery</b>	< 72 h/80% C for 18 Ah
<b>Weight of module PCB</b>	45 g
<b>Weight of the JA-83PWR power supply</b>	360 g
<b>PCB dimensions</b>	102 x 66 x 14 mm
<b>Power supply dimensions</b>	170 x 80 x 65 mm
<b>PLV-PC-L plastic housing dimensions</b>	357 x 297 x 105 mm PLV-PC-L plastic housing is not supplied!
<b>Classification</b>	security grade 2/environmental class II
<b>Note: valid for only installation into a PLV-CP-L plastic housing or into another box of a security grade 2 or higher certified device.</b>	
<b>- according to</b>	EN 50131-1, EN 50131-6
<b>- environment</b>	general indoor
<b>- operational temperature range</b>	-10 to +40 °C
<b>- operational humidity</b>	75 % RH, non-condensing
<b>- certification body</b>	Trezor Test s.r.o. (no. 3025)
<b>Also complies with</b>	EN 60950-1, EN 50130-4, EN 55022