

Network camera outdoor 5Mpx - bullet audio

Code: JI-114C-A

The outdoor bullet-style camera has an integrated speaker, microphone, and color LED diodes. It allows the user to trigger audio and visual alerts as needed from the MyJABLOTRON application.



Product description:

For continuous video recording, you can insert a memory card with a capacity of up **to 512 GB**.

Technical information:

| | |
|--|--|
| Power supply | from a PoE data connection (48V) (according to IEE standard 802.3af), max. power consumption: 7 W alternative powerpower connector 12 V DC, max. consumption: 5.8 W |
| Number of pixels | 5 Mpix |
| Camera resolutions and bitrates | 1-5 MPx, 448-3072 kbps (according settings in app) |
| Frames per second | 15 |
| Lens | 3.6 mm (88° angle of view) |
| Lens type | M12 plate lens |
| Sensing chip | 1/2.7" Progressive CMOS |
| WDR - half-light compensation | yes |
| Camera setup options | horizontal: 88°, Vertical: 48° |
| Communication interface | LAN |
| IR illumination range | 25 m |
| Environment | outdoor general |
| Operating temperature range | -35 °C to + 60 °C |
| Average operating humidity | up to 75 % non-condensing |
| Degree of protection | IP66 |
| Dimensions | 155 x o 71 mm |

Camera weight 358 g

Weight of socket 317 g

In compliance with EN 55032, EN 50130-4, EN IEC 63000
