

Wireless four-segment keypad with display and RFID reader - anthracite

Code: JA-155E-AN



The keypad is a wireless component of the JABLOTRON system. It serves for the controlling and displaying system status indication. It is equipped with four segments; their descriptions are displayed on the LCD display. The device should be installed by a trained technician with a valid certificate issued by an authorized distributor. The keypad is compatible with following control panels JA-102K, JA-103K, JA-107K and JA-152KR.

Technical information:

| | |
|--|---|
| Power supply | 4 x alkaline batteries, type: AA (LR6) 1.5 V Please note: Batteries are not included. |
| Typical lifetime of batteries | 1-2 Years |
| LowBatt state | <4.5 V |
| Quiescent current consumption (6 V) | 245 μ A |
| Maximum current consumption (6 V) | 115 mA |
| External power supply 12 V +/-1 V | typ. 45 mA, max. 100 mA |
| Communication band | 868.1 MHz, JABLOTRON protocol |
| Maximum radio-frequency power (ERP) | <25 mW |
| Communication range | approx 200 m (open area) |
| RFID frequency | 125 kHz |
| Dimensions | 110 x 136 x 33 mm |
| Weight (w/o batteries) | 285 g |
| Classification | Security grade 2/Environmental class II (according to EN 50131-1) |
| Environment | indoor general |
| Operating temperature range | -10 °C to +40 °C |
| Average operating humidity | 75% RH, w/o condensation |
| Certification body | Trezor Test s.r.o. (no. 3025) |
| In compliance with | ETSI EN 300 220-1,-2, ETSI EN 300 3300, EN 50130-4, EN 55032, EN 62368-1, EN 50581, EN 50131-1, EN 50131-3, EN 50131-5-3, EN 50131-6, |
| Operating conditions according to general authorization | ERC REC 70-03 |

Recommended screw

4 x o 3.5 x 40 mm (countersunk head)
