

# Network camera outdoor

## 5Mpx - bullet

Code: JI-114C

The outdoor camera in bullet design is very distinctive and visible. As a result, it acts partly as a deterrent against potential intruders.



### Technical information:

<b>Power supply</b>	from PoE data connection (48V) (according to IEE 802.3af standard) alternatively via 12 V DC power connector
<b>Rated current consumption</b>	250 mA
<b>Maximum current draw</b>	458 mA
<b>Number of pixels</b>	5 Mpix
<b>Camera resolutions and bitrates</b>	1-5 MPx, 448-3072 kbps (see setting in app)
<b>FPS</b>	15
<b>Lens</b>	3.6 mm (91° angle of view)
<b>Lens type</b>	M12 plate lens
<b>Sensing chip</b>	1/2.7" Progressive CMOS
<b>WDR - half-light compensation</b>	yes
<b>Camera setup options</b>	horizontal: 91°, Vertical: 46°
<b>Communication interface</b>	LAN
<b>IR illumination range</b>	30 m
<b>Environment</b>	outdoor general
<b>Operating temperature range</b>	-35 °C to +60 °C
<b>Average operating humidity</b>	up to 75 % non-condensing
<b>Degree of protection</b>	IP67
<b>Dimensions</b>	155 x o 71 mm
<b>Camera weight</b>	358 g
<b>Weight of socket</b>	317 g

---

**In compliance with**

EN 55032, EN 50130-4, EN IEC 63000

---