

Bi-directional four-button keyfob

Code: JA-154J MS II

It enables the remote control of the security system, plus various electric appliances, or triggering an emergency alarm. Confirmation of the execution of a command through optical and acoustic feedback.



Product description:

All this also with multiple JABLOTRON 100+ systems (e.g. at home and in the office).

The remote control can also be enrolled to a multi-functional relay of the AC-16x type to control the relay in accordance with the selected mode.

- The control is equipped with both optical and acoustic indication of the execution of a command.
- The control can be enrolled to multiple systems or multi-functional relays.
- It checks the status of its battery and indicates its being empty.
- If a key is pressed and held continuously, an activation is sent every second. This function can be used e.g. to extend the impulse of a PG output (e.g. the gradual closing of roller blinds).
- The sound of the keys can be switched off.
- The key lock function.
- Extended settings for double pressing the keys.
- The control is a device of the JABLOTRON 100+ system, is addressable and occupies one position in the system.

Technical information:

Compatible with:

FW of the JA-11xR radio module LR6x613+

FW of the control panel LJ(MD)60416+

F-Link 1.4.0+

Power - lithium battery

type CR 2032 (3.0 V/0.2 Ah)

(Power supply C type according to EN 50131-6)

Current consumption:

- Nominal consumption

1,1 µA

- Maximal consumption

33 mA

Low battery voltage detection

? 2.2 V

Typical battery lifetime

approx. 2 years (10 activations/day)

Communication frequency

868.1 MHz

Maximum radiofrequency output (ERP)

2 mW

RF range

approx 100 m (line of sight)

Dimensions	77 x 36 x 15 mm
Weight with no battery	35 g
Classification	Security grade 2/environmental class II in accordance to EN 50131-1
Environment	indoor general
Operational temperature range	-10 °C to +40 °C
Humidity	75 %, no condensation
Number of unique production codes	> 1 million
Certification body	Trezor Test s.r.o. (no. 3025)
Additionaly in compliance with	ETSI EN 300 220-1,-2, EN 50130-4, EN 55032, EN62368-1, EN50581, EN 50131-1, EN 50131-3, EN 50131-5-3, EN 50131-6
Can be operated according to	ERC REC 70-03