

Wireless PIR motion detector with basic pet immunity

Code: JA-154P PET

The JA-154P PET is a wireless PIR detector featuring basic pet immunity within the JABLOTRON 100+ and Mercury system portfolios. Serving as the direct successor to the popular JA-150P PET model, it utilises a proven standard design enhanced by a special lens that eliminates alarms caused by household pets.



Product description:

The detector is designed for standard indoor security in premises where small pets move along the floor and where reliable functionality at a reasonable price is a priority.

- **Basic pet immunity:** Special PET optics combined with digital signal processing minimise the risk of false alarms, ensuring trouble-free coexistence with animals in the home.
- **Two-way communication:** Utilises secure and reliable acknowledged communication with the system control panel.
- **Full remote configuration:** All detector settings are managed via configuration software (F-Link). This eliminates the need to visit the site or open the cover to access manual switches.
- **Effective power management:** Powered by two 1.5 V AA alkaline batteries with a typical service life of 4 years.
- **Comprehensive tamper protection:** The detector is equipped with sensors to detect both cover opening and removal from the wall.
- **Installation specifics:** For correct immunity performance, the device must be mounted on flat walls or in a corner at a height of 2.0 to 2.2 m.
- **System compatibility:** The product is fully compatible with [JA-102K](#), [JA-103K](#), [JA-107K](#), [JA-108K](#) series control panels, as well as [JA-152KRY](#) wireless variants.
- **Certified security:** The detector is certified to Security Grade 2 according to the EN 50131 standard.

Important Notice: Pet immunity has its limitations; detection may occur if an animal moves at height, such as a cat jumping onto a shelf level with the detector.

[Read more about basic PET immunity...](#)

Technical information:

| | |
|------------------------------------|---|
| Power supply | 2x alkaline batteries, type LR6 (AA) 1.5 V Note: batteries are not included. |
| Typical battery life | approximately 4 years |
| Low battery voltage | <2.4 V |
| Nominal current consumption | 36 µA |
| Maximum current consumption | 50 mA |
| Communication frequency | 868.1 MHz, JABLOTRON protocol |

| | |
|--|--|
| Maximum radio-frequency power (ERP) | <25 mW |
| Communication range | approx. 500 m (open terrain) |
| Recommended installation height | 2.2 m above floor level |
| Detection angle / detection coverage | 90 ° / 12 m (standard); 90 ° / 7 m (PET protection) |
| Dimensions | 60.8 x 97.5 x 51.8 mm |
| Weight (without batteries) | 82 g |
| Classification | security grade 2 / environment class II (according to EN 50131-1) |
| Environment | Indoor general |
| Operating temperature range | -10 °C to +40 °C |
| Average operating humidity | 75 % RH, non-condensation |
| Certification body | Trezor Test s.r.o. (No. 3025), Kiwa Nederland b. v. |
| Complies with | EN 50131-2-2, EN 50131-5-3, EN 50131-6, EN 50130-4, ETSI EN 300 220-2, EN 55032, EN IEC 62368-1, EN IEC 63000, T 031 |
| Operating conditions according to general authorisation | ERC REC 70-03 |
| Recommended screw | 2x ø 3.5 x 40 mm (countersunk head) |